

# VBA3100-50

800MHz - 3.1GHz 50W Amplifier

- High reliability proven GaAs design
- Class A for maximum mismatch drive
- General linear power requirements


The **VBA3100-50** is a member of our family of 800MHz-3.1GHz high power amplifiers, designed primarily for EMC applications.

Like all our products of the VBA3100 series, it is based on our GaAs technology, offering the user the benefits of linearity, ruggedness and efficiency. With its compression point close to saturated output, it is equivalent to TWT amplifiers of twice the output power.



The amplifier operates in class A, the benefits for EMC applications being very low distortion and tolerance of 100% mismatch. Fold-back protection is neither fitted nor needed! This makes it supremely suited for very demanding antenna and test chamber requirements.

## Performance Chart



Choose **GaAs Class A** for linearity, ruggedness, efficiency and cost.

**See overleaf for technical specification**

**Electrical**

<b>Frequency Range (Instantaneous)</b>	800-3100MHz
<b>Rated Output Power</b>	50W Min, 55W typical (800MHz-3.0GHz) 45W Min, 50W typical (3.0GHz-3.1GHz)
<b>Output Power at 1dB Gain Compression</b>	45W Min, 50W typical (800MHz-3.0GHz) 40W Min, 45W typical (3.0GHz-3.1GHz)
<b>Gain</b>	48dB Min
<b>Third Order Intercept Point (see note 1)</b>	57dBm
<b>Gain variation with Frequency</b>	±2dB
<b>Harmonics at 45W Output Power (800MHz-3.0GHz)</b>	Better than -20dBc
<b>Output Impedance</b>	50 Ohms
<b>Stability</b>	Unconditional
<b>Output VSWR Tolerance (see note 2)</b>	Infinity:1
<b>Input VSWR</b>	2:1 (Max)
<b>Supply Voltage</b>	85-264V ac
<b>Supply Frequency Range</b>	47-63Hz
<b>Supply Power</b>	<500VA (Max)
<b>Mains Connector</b>	IEC320

**Mechanical**

<b>RF Connector Style</b>	Type N Female
<b>Safety Interlock</b>	2 x BNC, S/C and O/C to Mute
<b>USB/GPIB Interface</b>	Optional
<b>Dimensions</b>	19 inch, 4U Case, 550mm Deep
<b>Mass</b>	20kg
<b>Operating Temperature Range</b>	0-40°C
<b>Case Style Options</b>	Rack mount with Front or Rear panel connectors Bench mount with Front panel connectors

**Regulatory Compliance**

<b>Conducted and Radiated Emissions</b>	EN61326 Class A
<b>Conducted and Radiated Immunity</b>	EN61326:1997 Table 1
<b>Safety</b>	EN61010-1

**Notes**

- 1 The third order intercept point is a nominal value, as its calculation depends upon the power level at which distortion measurements are made.
- 2 Output VSWR tolerance is specified for excitation within the permitted levels and frequency range

**Represented Worldwide**

**Vectawave Technology Ltd.**  
**Unit D, The Apex,**  
**St Cross Business Park, Monks Brook,**  
**Newport, Isle of Wight, PO30 5XW**

**Tel:** +44 (0) 1983 821 818

**Fax:** +44 (0) 1983 532 737

**E-mail:** sales@vectawave.co.uk